



Carpet

---

the tile company



Carpet Vestige 592x592



Carpet Sand 592x592

“Worn Axminster Carpet in a tile”

Carpet

thetilecompany

# Technical Specifications

| Type             | Use    | Made in | Brand   | Slip Rating | Variation | Print Faces |
|------------------|--------|---------|---------|-------------|-----------|-------------|
| Glazed Porcelain | Floors | Spain   | Aparici | R9          | V4        | 16          |

# Packaging

| Model   | Pieces/Box | m <sup>2</sup> /Box | Kg/Box | Boxes/Pallet | m <sup>2</sup> /Pallet | Kg/Pallet |
|---------|------------|---------------------|--------|--------------|------------------------|-----------|
| 592x592 | 4          | 1.4                 | 33     | 36           | 50.47                  | 1188      |

# Carpet

thetilecompany

| Version | Issue Date | Review Date | Prepared by                    |
|---------|------------|-------------|--------------------------------|
| 1.0     | 19/05/2026 | NA          | Stone & Tile Wholesale Limited |

Stone & Tile Wholesale Ltd trading as The Tile Company acts as the New Zealand supplier of products covered by this BPIR and is responsible for making product information available under the Building Product Information Requirements Regulations

# BPIR

**(Building product information requirements) - PAGE 1**

|                        |                                                                                                                          |
|------------------------|--------------------------------------------------------------------------------------------------------------------------|
| Product Name           | Carpet                                                                                                                   |
| Brand                  | Aparici                                                                                                                  |
| Product Type           | Floor—Porcelain                                                                                                          |
| Origin                 | Spain                                                                                                                    |
| Supplier International | Aparici— S.A. Carretera Castellon—Alcora, km 12. CP 12110 Alcora. Castellon. Spain—+34 964 70 10 10—contacto@aparici.com |
| Supplier NZ            | Stone & Tile Wholesale Limited—119B Montreal Street Christchurch—+64 3 962 2383—orders@stoneandtile.co.nz                |

**Products covered under this BPIR include all tiles listed within the Carpet collection unless otherwise stated.**

| Product        | Size    | Finish | Intended Use |
|----------------|---------|--------|--------------|
| Carpet Sand    | 592x592 | Matt   | Floor        |
| Carpet Vestige | 592x592 | Matt   | Floor        |

## Intended use

Products covered by this document may be suitable for:

- Interior floor applications
- Interior wall applications
- Residential use
- Commercial use where appropriate
- Wet area applications when correctly installed
- Exterior applications where products are specifically rated for outdoor use
- Access routes where products are selected to satisfy slip resistance requirements

Product suitability should be assessed against project-specific requirements and applicable New Zealand Building Code provisions.

## Supporting Documents

Supporting information may include:

- Technical data sheets
- Installation guides
- Slip resistance reports
- Fire performance documentation
- Care and maintenance guides
- Warranty documentation
- Product specifications
- (DOP) Declaration of Performance—Where available

Available upon request or via the Tile Company website [www.thetilecompany.co.nz](http://www.thetilecompany.co.nz)

|                                                              |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               |
|--------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Durability<br>B2:3.1                                         | Tiles supplied by The Tile Company are designed to provide long-term durability and performance under normal conditions of use. The Tile Company provides a 15-year product warranty subject to warranty terms, conditions, and correct installation practices.                                                                                                                                                                                                                                                                                                                                               |
| Fire Resistance<br>C3.4 (a) and (b)                          | Porcelain and ceramic tiles supplied by The Tile Company are inherently non-combustible and offer excellent resistance to heat and fire exposure under normal conditions of use. Where applicable, products may satisfy Group 1-S classifications and Critical Radiant Flux performance criteria under the New Zealand Building Code. Supporting documentation and test reports are available where applicable.                                                                                                                                                                                               |
| D1 Access Routes<br>D1.3.3                                   | Products identified as Anti-Slip, Structured, Grip, Slip Resistant, or similar may be suitable for applications requiring increased slip resistance. Slip testing may be undertaken using recognised testing methods, with supporting documentation available where applicable. Selection of suitable surfaces remains the responsibility of designers, specifiers, and installers based on intended use and project requirements.                                                                                                                                                                            |
| E3 Internal Moisture<br>E3.3.3<br>E3.3.4<br>E3.3.5<br>E3.3.6 | Glazed and full-body ceramic and porcelain products supplied by The Tile Company may provide durable and impervious finished surfaces suitable for wall and floor applications.<br>Most products exhibit low water absorption characteristics. Product-specific values are outlined in technical documentation.<br>Where products exceed 6% water absorption: <ul style="list-style-type: none"><li>• grout joints should be fully filled</li><li>• waterproofing systems should be used where required</li><li>• surfaces should remain free from defects that may compromise moisture performance</li></ul> |
| F2 Hazardous Building Materials                              | Porcelain and ceramic products supplied by The Tile Company are not expected to release harmful concentrations of substances or create health hazards under normal use conditions.                                                                                                                                                                                                                                                                                                                                                                                                                            |

Design Limitations

The following design considerations apply:

- Exterior installations should generally use porcelain products or products specifically approved for outdoor applications.
- Frost-prone applications require suitable low-water absorption products.
- Full immersion applications including pools and water features require porcelain products or products specifically approved for submerged use.
- Heavy impacts may chip or crack tile surfaces.
- Products with lower slip resistance classifications may not be suitable for external wet areas, ramps, swimming pool surrounds, commercial kitchens, access routes, or other applications requiring increased slip resistance performance. Product suitability should be assessed against intended use and applicable New Zealand Building Code requirements.
- Slip resistant surfaces require regular cleaning and maintenance.
- Tile selection should consider substrate movement, loading, environmental exposure, and intended use.

Installation Requirements

Products should be installed:

- by suitably qualified installers
- in accordance with manufacturer recommendations
- to current Australian and New Zealand tiling standards
- following recognised industry practice
- with suitable substrate preparation and waterproofing systems where required

Relevant guidance may include:

BRANZ Good Practice Guide: Tiling

AS 3958 Ceramic Tiles Installation Standard

Manufacturer installation documentation

Maintenance Requirements

Regular maintenance is recommended to preserve performance and appearance.

Cleaning should:

- use pH-neutral cleaning products
- avoid harsh acids and abrasive products
- follow The Tile Company Maintenance and Care Guide

Slip resistant and textured surfaces may require additional maintenance.

Technical Performance Information

Floor

| Property         | Value                                    |
|------------------|------------------------------------------|
| Type             | Glazed Porcelain                         |
| Thickness        | 10mm                                     |
| Water Absorption | ≤0.5%                                    |
| Slip Rating      | R9                                       |
| Frost Resistance | Yes                                      |
| Shade Variation  | V4                                       |
| Faces            | 16                                       |
| Rectified        | No                                       |
| Application      | Indoor Residential & Commercial Flooring |